

# LP-AW4001 / LP-AW3001

Our first ever 3LCD Laser Ultra Short Throw Projectors



**PJLink™**

**CRESTRON**

**Extron  
CERTIFIED**

**Laser**

**HDMI™**  
HIGH DEFINITION MULTIMEDIA INTERFACE

**AMX**

**3LCD**

**Introducing our highly innovative new 3LCD LP-AW4001 / LP-AW3001 laser projectors which combines all our technical expertise with our market leading knowledge.**

This new 3LCD projector is environmentally friendly as it contains no mercury lamp, provides a significant reduction in maintenance costs, as this new laser diode light source offers approx. 20,000 hours of operation time.

This new ultra-short throw projector can reach up to 4,200 ANSI lumens by using our highly efficient optical engine, providing clarity on images even within very bright / light environments.

#### Key Features:

Approx. 20,000 hours maintenance free operation for laser light source

WXGA 1280 x 800 resolution

Up to 4,200 ANSI lumens white/colour output

500,000:1 Contrast Ratio

Wide screen, images up to 130" diagonal

Accentualizer - advanced image processing


High Dynamic Contrast Range (HDCR)

# LP-AW4001 / LP-AW3001 3LCD Laser Ultra Short Throw Projectors

## Technical Specifications

<b>Panel Size</b>	3 LCD 15mm (0.59" )
<b>Panel Structure</b>	3LCD
<b>Resolution</b>	WXGA (1280 x 800)
<b>Light Output (Brightness) ANSI Lumens</b>	LP-AW4001: 4200 (Normal) / LP-AW3001: 3300 (Normal)
<b>Contrast Ratio</b>	500,000:1
<b>System (Hours)</b>	20,000
<b>Lens</b>	Built-in
<b>Lens Zoom</b>	Digital zoom x 1.35
<b>Lens Focus</b>	Powered focus
<b>Projection Lens F Number</b>	1.6
<b>Throw Distance</b>	0.488m – 0.978m (centre of glass to screen)
<b>Distance to Width Ratio/ Throw Ratio (:1)</b>	0.3
<b>Diagonal Display Size</b>	60 - 130"
<b>Installation</b>	Ceiling, Tabletop, Rear
<b>Speakers</b>	16W mono
<b>Digital Keystone Correction (Degrees)</b>	Horizontal: ± 5° / Vertical: ± 5°
<b>Picture Modes</b>	Normal, Cinema, Dynamic, Whiteboard, DICOM SIM, User-1, User-2, User-3
<b>Picture Adjustments</b>	ASPECT selection (normal/4:3/16:9/16:10/14:9/zoom/native), Perfect fit (4 corners and 4 sides), Frame lock (data signal with vertical frequency of 49 to 51 Hz, 59 to 61 Hz), HDCR, Image blank by RS232C/remote control, Image optimizer, Magnify, Mirror reverse Image, Up-side down image
<b>Operating Features</b>	Keystone V/H, PerfectFit, Standby audio, Audio pass through, Cloning function, Easy schedule setting
<b>Network Features</b>	Wireless capability(Optional), Multi projector, Moderator control mode (TBC), Projector quick connection (iOS / Android app), Projector monitoring and Control from a remote location, E-mail Alerts
<b>Security Features</b>	Password/Myscreen Password, Pin Lock, Key Lock
<b>Supported Languages</b>	34 Languages (English, French, German, Spanish, Italian, Norwegian, Dutch, Japanese, Portuguese, Simplified Chinese, Traditional Chinese, Korean, Swedish, Russian, Finnish, Polish, Turkish, Arabian, Persian, Czech, Danish, Hungarian, Romanian, Slovenian, Croatian, Greek, Lithuanian, Estonian, Latvian, Thai, Portuguese (Brazil), Indonesian, Vietnamese, Hebrew)
<b>Digital Input</b>	HDMI x 2 (HDCP compliant, HDMI 1 shared with MHL)
<b>Analogue Input</b>	15-pin Mini-D-Sub x 2, RCA Jack x 1
<b>Video Output</b>	15-pin Mini-D-Sub x 2, RCA Jack x 1
<b>Audio Input</b>	3.5mm Stereo Mini Jack x 3
<b>Audio Output</b>	3.5mm Stereo Mini Jack x 1
<b>RS-232C Control</b>	1 x 9-pin D-Sub
<b>Wireless LAN</b>	USB-WL-5G (IEEE802.11 a/b/g/n/ac: 2.4GHz/5GHz) (Optional)
<b>Wired LAN</b>	RJ45 connector x 1
<b>USB Type-A</b>	USB type A x 2 (PC less Presentation or Wireless adapter)
<b>USB Type B</b>	USB type B x 1 (USB display or USB mouse control)
<b>Power Supply</b>	AC 100V – 120V / AC 220V – 240V (50/60Hz)
<b>Operating Power Consumption</b>	LP-AW4001: 350W / LP-AW3001: 280W
<b>Standby Power Consumption</b>	Less than 0.5W
<b>Weight</b>	LP-AW4001: 7.6Kg / LP-AW3001: 7.4Kg
<b>Dimensions (W x H x D)</b>	512 x 424 x 155mm
<b>Noise (Normal)</b>	34dB (Normal), 28dB (Eco)
<b>Filter Life (Hours)</b>	20,000
<b>Certification</b>	TBD

<b>Computer</b>	IBM Compatible VGA, SVGA, XGA, WXGA, WXGA+/SXGA/SXGA+/UXGA (compressed)
<b>Video</b>	525i(480i), 525p(480p), 625i(576i), 625p(576p)1125i(1080i@50/60), 1125p(1080p@50/60)
<b>Supplied Accessories</b>	Remote control: HL03037, Power cable, Computer cable, User's manual, Concise, Security label, Adapter cover, Hook metal, Screw, HDMI cable holder (x2), Cable tie (large x 1, medium x 2, small x 1), AA batteries (x2)
<b>Optional Accessories</b>	USB Wireless adaptor USB-WL-5G, Wall mount unit HAS-WM06 (In some buying conditions wall mount is included)
<b>Remote Control</b>	HL03037
<b>Projector/ Light source Warranty</b>	20,000 hours / 5 years (whichever comes first) (for extended warranties please contact your local dealer)



**HITACHI**  
Inspire the Next

Hitachi Digital Media

Hitachi Europe Ltd, Whitebrook Park, Lower Cookham Road,  
Maidenhead, Berkshire SL6 8YA, United Kingdom

Tel: +44 (0)1628 585 000 / Fax: +44 (0)1628 585 163

www.hitachidigitalmedia.com