



Document Manager

- Compact multifunctional A3 colour system – ideal for up-and-coming businesses
- Excellent colour quality and flexible finishing options which meet your needs
- Individual templates on LCD and in printer driver to allow for efficient and productive workflows
- Environment friendly thanks to improved toner technology

e-STUDIO2050c
e-STUDIO2550c



SAP® Printer Vendor Solution





e-STUDIO2050c
e-STUDIO2550c



General	Print & Copy Speed Warm-up Time Paper Size & Weight Paper Capacity Automatic Duplex Controller Type Control Panel Memory Interface Dimensions & Weight	20/25 ppm (A4), 10/12 ppm (A3) Approx. 15 seconds (from low power mode) Cassettes: A5R-A3, 60-163 g/m² Large Capacity Feeder¹⁾: A4, 60-163 g/m² Bypass: 100 x 148 mm-A3, 60-209 g/m² 250 sheets (Cassettes), 100 sheets (Bypass) Maximum: 2,900 sheets A5R-A3, 60-163 g/m² Toshiba e-BRIDGE 9" (22.8 cm) colour touch panel LCD 8 GB SSD / 2 GB RAM, 160 GB Toshiba Secure HDD^{1) 2)} 10/100/1000BaseT (incl. IPv6), High Speed USB 2.0, WLAN¹⁾ (IEEE802.11b/g) 575 x 590 x 662 mm (W x D x H), ~ 57 kg
Print	Resolution Page Description Languages Supported Systems Print Functions	Max. 600 x 600 dpi (5 bit), 600 x 1,200 dpi (1 bit) XPS, PCL6 and PostScript 3 compatible Windows 7/Vista/XP/Server 2008/Server 2003 (32/64 bit), Windows Server 2008 R2 (64 bit), Mac OS X, Linux/UNIX, Novell Netware (NDPS), Citrix, SAP, AS/400 Universal Driver, Driver templates, Driver plug-ins, Hold print³⁾, Print from USB, Tandem printing
Scan	Resolution Scan Speed Scan Modes File Formats Scan Functions	Max. 600 x 600 dpi Up to 50 ipm (300 dpi) Auto-Colour (ACS), Colour, Greyscale, B&W JPEG, Multi/Single Page TIFF/XPS³⁾/PDF, Slim PDF, Secure PDF, Searchable PDF¹⁾ (and other formats like DOC, XLS, RTF, TXT, PDF/A)¹⁾ Web Services Scan (pull/push), Scan to USB, Scan to E-Mail, Scan to File (SMB, FTP, FTPS, IPX/SPX, local³⁾), Meta Scan¹⁾, Scan to Box (e-Filing³⁾), Remote TWAIN, TWAIN1.7/1.8/1.9³⁾
Copy	Resolution First Copy Zoom Copy Modes	Max. 600 x 600 dpi Approx. 8.2 seconds 25-400% (platen), 25-200% (RADF)¹⁾ Text, Text/Photo, Photo, Printed Image, Map
Fax¹⁾	Communication Transmission Speed Compression Fax Memory Network-Fax Incoming Fax Routing	Super G3, G3 (opt. 2nd line), Internet Fax T.37 Approx. 3 seconds per page JBIG, MMR, MR, MH 100 MB (SSD)/1 GB (HDD)¹⁾ Transmission/Reception Driver for Windows 7/Vista/XP/Server2008 R2 To shared folders (SMB, FTP, IPX/SPX), E-mail, e-Filing³⁾
System & Security	Device Management System Features Accounting & Security	e-BRIDGE Fleet Management System¹⁾, TopAccess for remote administration and configuration e-Filing³⁾ document server for secure storage, document distribution and Print on Demand (1 public box, 200 user boxes), 60/12,060³⁾ One- touch Templates for storage of personalised settings or workflows, e-BRIDGE Open Platform¹⁾, Embedded Web Browser, Job Skip³⁾ Role Based Access, LDAP support, 50/1,000³⁾ department codes & 100/10,000³⁾ user codes, card reader¹⁾, private print³⁾, standard data encryption with Toshiba Secure HDD³⁾, Data Overwrite Enabler^{1) 3)}, IP and MAC address filter, port filter, support of SSL and IPsec¹⁾ protocols, IEEE802.1x support¹⁾, IEEE2600.1 compliant^{1) 3)}, Scan to Secure PDF

¹⁾ Optional

²⁾ 1GB = 1 billion bytes; the actual formatted capacity is less. Available capacity will also be less if software applications are pre-installed.

³⁾ Requires Toshiba Secure HDD

Productivity and paper specifications are related to a paper size of A4 and a paper weight of 80 g/m² if not otherwise mentioned.

OPTIONS

PLATEN COVER – KA-1640PC

RADF – MR-3024

100-sheet capacity, A5R-A3, 35-157 g/m²

JOB SEPARATOR TRAY – MJ-5004

2 inner trays, 150- and 250-sheet capacity

INNER FINISHER – MJ-1036

2 trays, 600-sheet capacity
50-sheet multi-position stapling
482 x 508 x 232 mm (W x D x H), ~ 15.3 kg

SADDLE-STITCH FINISHER – MJ-1037

1 tray, 1,000-sheet capacity
50-sheet multi-position stapling
Saddle-stitched booklets of up to 60 pages
575 x 492 x 942 mm (W x D x H), ~ 37 kg

HOLE PUNCH UNIT – MJ-6007/MJ-6008

Options for Finisher MJ-1036/MJ-1037
Available in 2-holes (E), 4-holes (F/S)
120 x 245 x 597 mm (W x D x H), ~ 3.3 kg
126 x 463 x 174 mm (W x D x H), ~ 3.4 kg

PAPER FEED UNIT – MY-1040

550 sheets (1 drawer), A5R-A3, 60-163 g/m²
575 x 583 x 163 mm (W x D x H), ~ 9.5 kg

PAPER FEED PEDESTAL – KD-1032

550 sheets (1 drawer), A5R-A3, 60-163 g/m²
668 x 701 x 292 mm (W x D x H), ~ 16.3 kg

LARGE CAPACITY FEEDER – KD-1031A4

2,000-sheet capacity, A4, 64-105 g/m²
668 x 735 x 292 mm (W x D x H), ~ 26 kg

OTHER OPTIONS

DESK – MH-2050

PAPER FEED CONTROLLER – GH-1080

DRAWER MODULE – MY-1039

TOSHIBA SECURE HDD 160 GB²⁾ – GE-1220

FAX BOARD – GD-1320EU

FRONT USB KIT – GR-1140

WORK TRAY – KK-4550

DATA OVERWRITE ENABLER – GP-1070³⁾

e-BRIDGE ID-GATE – KP-2004/5, TWN3XX

WIRELESS LAN MODULE – GN-1060

META SCAN ENABLER – GS-1010

IPsec ENABLER – GP-1080

UNICODE FONT ENABLER – GS-1007³⁾

e-BRIDGE RE-RITE – GB-1280

ACCESSIBLE ARM – KK-2550

TOSHIBA TEC GERMANY
IMAGING SYSTEMS GMBH

CARL-SCHURZ-STRASSE 7 · D-41460 NEUSS
TEL. +49(0)2131-12450, FAX +49(0)2131-1245402
WWW.TOSHIBA-EUROPE.COM/TEC

TOSHIBA
Leading Innovation >>>

Technical data is subject to change without prior notice. All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries. All rights reserved. We are constantly making efforts to deliver the latest status of data to our partners. Specifications for some models may change in the time between the production and the release of this documentation. Copyright © 2012 TOSHIBA TEC. DS2550cGBEMD1202