



Document Manager

- Efficient, fast and easy office document communication for departmental workgroups.
- Latest Toshiba e-BRIDGE technology at 25/30 pages per minute for reliable and exceptional ease-of-use in B&W print, copy, fax, and Colour-Scan.
- Reduced energy consumption in sleep mode – only 1 watt power is used.
- Efficient internal toner recycling system saves cost and resources.

e-STUDIO255
e-STUDIO305





e-STUDIO255
e-STUDIO305



General	<p>Print & Copy Speed 25/30 ppm (A4), 16/16 ppm (A3) Approx. 20 seconds</p> <p>Warm-up Time Cassettes: A5R-A3, 64-105 g/m²</p> <p>Paper Size & Weight Large Capacity Feeder*: A4, 64-105 g/m² Bypass: A5R-A3, 52-209 g/m² 2 x 550 sheets (Cassettes), 100 sheets (Bypass) Maximum: 3,200 sheets</p> <p>Paper Capacity A5R-A3, 64-105 g/m²</p> <p>Automatic Duplex Controller Type Toshiba e-BRIDGE</p> <p>Control Panel Tilttable with 8.5" colour touch panel LCD</p> <p>Memory 60 GB HDD / 1 GB RAM</p> <p>Interface 10/100BaseT (incl. IPv6), High Speed USB 2.0, WLAN* (IEEE802.11b/g), Bluetooth*</p> <p>Dimensions & Weight 575 x 586 x 756 mm (W x D x H), ~ 63 kg</p>	
Print	<p>Resolution Max. 2,400 x 600 dpi with smoothing</p> <p>Page Description Languages XPS, PCL6 and PostScript 3 compatible</p> <p>Supported Systems Windows 2000, Windows Vista/XP/Server 2008/Server 2003 (32/64 bit), Mac OS X, Linux/Unix, Novel NetWare, Citrix, SAP, AS/400</p>	
Scan	<p>Resolution Max. 600 x 600 dpi, colour (8 Bit) or mono</p> <p>Scan Speed Up to 57/43 (mono/colour) spm (300 dpi)</p> <p>Document Feeder* Max. 100 sheets, A5R-A3, 35-157 g/m²</p> <p>Scan Modes Auto-Colour (ACS), Colour, Greyscale, B&W</p> <p>File Formats JPEG, Multi/Single Page TIFF/XPS/PDF, Slim PDF, Secure PDF, Searchable PDF* (and other editable formats like DOC, XLS, RTF, TXT)*</p> <p>Scan Functions Web Services Scan (pull/push), Scan to USB, Scan to E-Mail, Scan to File (SMB, FTP), Meta Scan*, Scan to Box (e-Filing), TWAIN1.7</p>	
Copy	<p>Resolution Max. 2,400 x 600 dpi with smoothing</p> <p>First Copy Approx. 4.7 seconds</p> <p>Zoom 25-400% (platen glass), 25-200% (RADF*)</p> <p>Copy Modes Text, Text/Photo, Photo, Colour Document, Custom</p>	
Fax*	<p>Communication Super G3, G3 (opt. 2nd line), Internet Fax T.37</p> <p>Transmission Speed Approx. 3 seconds per page</p> <p>Compression JBIG, MMR, MR, MH</p> <p>Fax Memory TX 500 MB (HDD), RX 200 MB (HDD)</p> <p>Network-Fax Driver for Windows 2000, XP/Vista (32/64 bit)</p> <p>Incoming Fax Routing To shared folder (SMB, FTP), e-mail, e-Filing</p>	
System & Security	<p>Device Management e-BRIDGE Fleet Management Software*, TopAccess remote administration & configuration</p> <p>System Features e-Filing document server for secure storage, document distribution and Print on Demand (1 public box, 200 user boxes), 12,060 One- touch templates for storage of personalised settings or workflows, Print from USB, e-BRIDGE Open Platform*</p> <p>Accounting & Security Role Based Access, LDAP support, 1,000 department codes & 10,000 user codes, card reader support*, private/hold print, standard data encryption, Data Overwrite Enabler*, IP and MAC address filter, port filter, support of SSL and IPSec* protocol, IEEE802.1x support, Scan to Secure PDF</p>	
<p>* Optional</p> <p>Productivity and paper specifications are related to a paper size of A4 and a paper weight of 80 g/m² if not otherwise mentioned.</p>		

OPTIONS

RADF – MR-3021

100 sheet capacity, A5R-A3, 35-157 g/m²

JOB SEPARATOR TRAY – MJ-5004

2 inner trays, 150 and 250 sheet capacity

OFFSET TRAY – MJ-5005

250 sheets capacity

HANGING FINISHER – MJ-1031

1 tray, 1,000 sheet capacity
50 sheet single position stapling
411 x 595 x 383 mm (W x D x H), ~ 12 kg

SADDLE-STITCH FINISHER – MJ-1025

1 trays, 1,000 sheet capacity
50 sheets multi-position stapling
Saddle-stitched booklets of up to 40 pages
538 x 603 x 1,011 mm (W x D x H), ~ 38 kg

HOLE PUNCH UNIT – MJ-6005

Option for Finisher MJ-1025
Available in 2-holes (E), 4-holes (F/S)
90 x 560 x 170 mm (W x D x H), ~ 4 kg

PAPER FEED PEDESTAL – KD-1025

550 sheet (1 drawer), A5R-A3, 64-105 g/m²
668 x 701 x 291.5 mm (W x D x H), ~ 21 kg

LARGE CAPACITY FEEDER – KD-1026A4

2,000 sheet capacity, A4, 64-105 g/m²
668 x 737 x 291.5 mm (W x D x H), ~ 25 kg

e-BRIDGE RE-RITE – GB-1280

OCR Server Software adding editable and
text-searchable file formats to scan function

OTHER OPTIONS

DESK MH-2520
DRAWER MODULE MY-1033
FAX BOARD GD-1250EU
E-BRIDGE ID-GATE KP-2004/KP-2005
WIRELESS LAN MODULE GN-1050
BLUETOOTH MODULE GN-2010
DATA OVERWRITE ENABLER GP-1070
META SCAN ENABLER GS-1010
WEB-SERVICES ENABLER GS-1020
ACCESSIBLE ARM KK-2550

TOSHIBA TEC GERMANY
IMAGING SYSTEMS GMBH

CARL-SCHURZ-STRASSE 7 · D-41460 NEUSS
TEL. +49(0)2131-12450, FAX +49(0)2131-1245402
WWW.TOSHIBA-EUROPE.COM/TEC

TOSHIBA
Leading Innovation >>>

Technical data is subject to change without prior notice. All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries. All rights reserved. We are constantly making efforts to deliver the latest status of data to our partners. Specifications for some models may change in the time between the production and the release of this documentation. Copyright © 2009 TOSHIBA TEC. DS3055BNE0903