







## Document Manager

- All-in-one A3 colour system for small offices and workgroups
- Up to five different paper sources, which can handle various paper sizes
- Intuitive handling via LCD touch screen for utmost user-friendliness
- Improved toner technology for environmental friendly printing

## **€**-**STUDIO**2051**c €**-**STUDIO**2551**c**











General	Print & Copy Speed Warm-up Time Paper Size & Weight Paper Capacity  Automatic Duplex Controller Type Control Panel Memory Interface Dimensions & Weight	20/25 ppm (A4), 10/12 ppm (A3) Approx. 15 seconds (from low power mode) Cassettes: A5R-A3, 60-163 g/m² Bypass: 100 x 148 mm-A3, 60-209 g/m² 250 sheets (Cassettes), 100 sheets (Bypass) Maximum: 2,000 sheets A5R-A3, 60-163 g/m² Toshiba e-BRIDGE 7" (17.8 cm) colour touch panel LCD 8 GB SSD / 2 GB RAM 10/100/1000BaseT (incl. IPv6), High Speed USB 2.0 575 x 590 x 662 mm (W x D x H), ~ 56 kg
Print	Resolution Page Description Languages Supported Systems  Print Functions	Max. 600 x 600 dpi (5 bit) PCL6 compatible Windows 7/Vista/XP/Server 2008/Server 2003 (32/64 bit), Windows Server 2008 R2 (64 bit), Novell Netware (NDPS), Citrix Universal Driver, Driver templates, Driver plug-ins, Tandem printing
Scan	Resolution Scan Speed Scan Modes File Formats Scan Functions	Max. 600 x 600 dpi Up to 50 ipm (300 dpi) Auto-Colour (ACS), Colour, Greyscale, B&W JPEG, Multi/Single Page TIFF/PDF, Slim PDF, Secure PDF Web Services Scan (pull/push), Scan to USB, Scan to E-Mail, Scan to File (SMB, FTP, FTPS, IPX/SPX), Remote TWAIN
Сору	Resolution First Copy Zoom Copy Modes	Max. 600 x 600 dpi Approx. 8.2 seconds 25-400% (platen), 25-200% (RADF) <sup>1)</sup> Text, Text/Photo, Photo, Printed Image, Map
Fax¹ <sup>1</sup>	Communication Transmission Speed Compression Fax Memory Network-Fax Incoming Fax Routing	Super G3, G3 (opt. 2 <sup>nd</sup> line), Internet Fax T.37 Approx. 3 seconds per page JBIG, MMR, MR, MH 100 MB (SSD) Transmission/Reception Driver for Windows 7/Vista/XP/Server2008 R2 To shared folders (SMB, FTP, IPX/SPX), E-mail
System & Security	Device Management  System Features Accounting & Security	e-BRIDGE Fleet Management System <sup>1)</sup> , TopAccess for remote administration and configuration 60 One-touch Templates for storage of personalised settings or workflows Role Based Access, LDAP support, 50 department codes & 100 user codes, card reader <sup>1)</sup> , IP and MAC address filter, port filter, support of SSL protocols, Scan to Secure PDF

**OPTIONS** 

PLATEN COVER - KA-1640PC

**RADF - MR-3024** 

100-sheet capacity, A5R-A3, 35-157 g/m<sup>2</sup>

JOB SEPARATOR TRAY - MJ-5004

2 inner trays, 150- and 250-sheet capacity

PAPER FEED UNIT - MY-1040

550 sheets (1 drawer), A5R-A3, 60-163 g/m<sup>2</sup> 575 x 583 x 163 mm (W x D x H), ~9.5 kg

PAPER FEED PEDESTAL - KD-1032

550 sheets (1 drawer), A5R-A3, 60-163 g/m² 668 x 701 x 292 mm (W x D x H),  $\sim$  16.3 kg

**OTHER OPTIONS** 

DESK – MH-2050 PAPER FEED CONTROLLER – GH-1080 DRAWER MODULE – MY-1039 FAX BOARD – GD-1320EU WORK TRAY – KK-4550

e-BRIDGE ID-GATE – KP-2004/5, TWN3XX e-BRIDGE RE-RITE – GB-1280 Technical data is subject to change without prior notice. All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries. All status of data to our partners. Specifications for some models may change in the time between the production and the release of this documentation. Copyright © 2012 TOSHBA TEC. DS2551cGBEMD1202

ACCESSIBLE ARM – KK-2550

1) Optional

Productivity and paper specifications are related to a paper size of A4 and a paper weight of  $80~g/m^2$  if not otherwise mentioned.

TOSHIBA