3752RK

Creative Touch 3-Series 75" interactive flat panel display

Optoma





- Advanced interaction and collaboration -CreativeCast Pro interactive wireless collaboration toolset
- Advanced touch technology Pen and finger recognition for a seamless experience
- Dual App mode Run two applications at the same time on the screen
- Safe and secure viewing experience Anti glare and anti finger print, low blue light and flicker free TUV certified

Robust collaboration, extensive connectivity options and a valuefocused design. Combining the latest technology and packed with everything a classroom or business requires, the Creative Touch 3-Series delivers all the functionalities and processing power needed to create, educate and collaborate.



Easily access the front-facing ports for HDMI and USB connectivity. For wireless connectivity, Optoma's CreativeCast Pro allows up to four users to share content at the same time from their Windows, iOS, macOS, Chrome or Android devices.

Specifications

Display	
Back light	Direct type LED
Size (diagonal)	75"
Resolution	3840x2160
Brightness Contrast ratio (dynamic)	400 5.000:1
/iewing angle	178°
Response time	6ms
life	50.000 hours
Display colours	1,070
Speaker count	2
Vatts per speaker	20W
Surface hardness	9H
alass	Anti Glare + Anti Finger Print / HAZE: 4-8%
mbient light sensor	Yes
\ir gap	4.00mm
Pencil hardness	9H
Physical spec	
Dimensions (W x D x H) mm	1735 x 116 x 1047
Vall-hanging screw spec	M8*25mm
ESA holes n the box	800x400 European Standard Rower Cord 5M
in the box	European Standard Power Cord 5M American Standard Power Cord 5M
	British Standard Power Cord 5M
	USB Touch Cable 3M
	USB-C Cable 2M HDMI Cable
	Writing Pen x2
	Remote Control
	Battery
	Pen holder/ Pen tray QSG
Connections	
	Inputs 3 x HDMI 2.0, 1 x VGA, 1 x DisplayPort, 1 x Audio 3.5mm, 4 x USB 2.0, 1 x USB 3.0, 1 x RJ45, 1 x USB-C, 1 x Microphone
	Outputs 1 x HDMI 2.0, 1 x S/PDIF, 1 x Audio 3.5mm, 1 x
	RJ45
	Control 2 x USB-B interactive, 1 x RS232
ezel size (top)	22.00mm
sezel size (bottom)	54.00mm
Bezel size (left)	22.00mm
lezel size (right)	22.00mm
perating conditions	20% ~ 93% RH
Dperating temperature (min)	-10°C
perating temperature (max)	45°C
let weight	51 kg
aross weight	65 kg
Vireless - technology	Wifi 6, 2.4G/5G, 2T2R, BT5.2 (AZ832-HN optional)
Vireless - operating frequency	2.4G/5G
ouch system	
ystem	Windows10/Windows8/Windows7/Windows XP /Linux/Mac (1 Touch point only)/Android/Chrome
ouch accuracy	<1.00mm
ouch point	< 1.00mm 20 android / 40 windows
ouch tool	Finger, Passive infrared pen
en/finger detection	Yes
Power	
ower supply	100-240V~ 50/60Hz 3.5A
ower consumption (standby)	0.5W
ower consumption (max)	400W
ower consumption - average	153.1
vatts)	
peration System	
system version	Android 11
CPU	Quad-core A55
λPU	Dual-cord A52
RAM	4GB
Storage	32GB
OD / disculated	21 languages: Arabic, Czech, Danish, Dutch, English, Finnish,
OSD / display languages	French, German, Greek, Hungarian, Italian, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish,







Copyright © 2023, Optoma and its logo is a registered trademark of Optoma Corporation. Optoma Europe Ltd is the licensee of the registered trademark. All other product names and company names used herein are for identification purposes only and may be trademarks or registered trademarks of their respective owners. Errors and omissions excepted, all specifications are subject to change without notice. All images are for representation purposes only and may be simulated. 15082023121513